



# Accentline

## Accentline 20W GU5.3 12V 36D 1CT/10X5F


Low-voltage halogen burner in glass reflector. Ideal solution for small decorative luminaires, putting your objects in the spotlight. Dichroic coating prevents heat transmission onto the object.

### Product data

General Information	
Cap-Base	GU5.3 [ GU5.3]
Philips Code	14596
Operating Position	UNIVERSAL [ Any or Universal (U)]
ANSI Code Halogen	BAB
Nominal Lifetime (Nom)	2000 h
Switching Cycle	8000X
Light Technical	
Beam Angle (Nom)	36 °
Luminous Intensity (Max)	400 cd
Rated Beam Angle	36 °
Correlated Color Temperature (Nom)	3000 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	20 W
Lamp Current (Nom)	1.67 A
Starting Time (Nom)	0.0 s
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Label (EEL)	B
Luminaire Design Requirements	
Cap-Base Temperature (Max)	250 °C
Product Data	
Full product code	871150041199000
Order product name	Accentline 20W GU5.3 12V 36D 1CT/10X5F
EAN/UPC - Product	8711500411990
Order code	926000850033
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	926000850033
Net Weight (Piece)	0.032 kg
ILCOS Code	HRGI-50-12-GU5.3-20/36

## Dimensional drawing



Product	D (max)	C (max)
Accentline 20W GU5.3 12V 36D 1CT/10X5F	51 mm	46 mm

FIGHTER 14596 20W GU5.3 12V MR16 36D

## Photometric data

