



MASTER TL-D 90 De Luxe

MASTER TL-D 90 De Luxe 58W/940 SLV/10

This TL-D lamp makes colors appear rich, deep and enhanced in a natural way. Thus very suitable for applications where a high color recognition is needed: first aid and treatment rooms in hospitals, printing rooms, jewelry, dentists, hairdressing, museums and shops

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Lamp Current (Nom)	0.670 A
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Controls and Dimming	
Life to 50% Failures (Nom)	15,000 hour(s)	Dimmable	Yes
Light Technical		Mechanical and Housing	
Color Code	940 [CCT of 4000K]	Bulb Shape	T8
Luminous Flux	4,600 lm	Approval and Application	
Luminous Efficacy (rated) (Nom)	76.9 lm/W	Energy Consumption kWh/1000 h	68 kWh
Color Designation	Cool White (CW)	Mercury (Hg) Content (Nom)	1.7 mg
Chromaticity Coordinate X (Nom)	0.38	Product Data	
Chromaticity Coordinate Y (Nom)	0.38	Order product name	MASTER TL-D 90 De Luxe 58W/940 SLV/10
Correlated Color Temperature (Nom)	4000 K	Full product name	MASTER TL-D 90 De Luxe 58W/940 SLV/10
Color rendering index (CRI)	91	Full product code	871150088869325
Operating and Electrical			
Power Consumption	58.5 W		

MASTER TL-D 90 De Luxe

Order code	928045094081
Material Nr. (12NC)	928045094081
Net Weight (Piece)	167.000 g
EAN/UPC - Product/Case	8711500888693


Numerator - Packs per outer box	10
EAN/UPC - Case	8711500888709

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D 90 De Luxe 58W/940 SLV/10	28 mm	1,500.0 mm	1,507.1 mm	1,504.7 mm	1,514.2 mm

Photometric data




Spectral Power Distribution Colour - MASTER TL-D 90 De Luxe 58W/940 SLV/10

Lifetime




Life expectancy diagram - 12 hour cycle



Life expectancy diagram - 3 hour cycle

MASTER TL-D 90 De Luxe

Lifetime



Lumen Maintenance Diagram - MASTER TL-D 90 De Luxe 58W/940 SLV/10

