



MASTER TL5 Circular



55 W 2GX13 Warm white Circular fluorescent

This circular TL5 lamp (tube diameter 16 mm) offers extended design possibilities. The slim tube allows the creation of extremely flat luminaires and enables omnidirectional light distribution. It is suitable for a wide range of professional and semi-professional applications, and is ideal for use in shops, offices and public areas with unconventional layouts.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Lamp Current (Nom)	
Cap-Base	2GX13	0.550 A	
Nominal lifetime	12,000 hour(s)	Controls and Dimming	
Flux measurement reference	Sphere	Dimmable	Yes
Light Technical		Mechanical and Housing	
Color Code	830 [CCT of 3000K]	Bulb Shape	C-T5
Luminous Flux	4,210 lm	Approval and Application	
Luminous Efficacy (rated) (Nom)	76 lm/W	Energy Efficiency Class	G
Color Designation	Warm White (WW)	Mercury (Hg) Content (Max)	4 mg
Chromaticity Coordinate X (Nom)	0.44	Mercury (Hg) Content (Nom)	4 mg
Chromaticity Coordinate Y (Nom)	0.403	Energy Consumption kWh/1000 h	56 kWh
Correlated Color Temperature (Nom)	3000 K	EPREL Registration Number	423622
Color rendering index (CRI)	81	Product Data	
Operating and Electrical		Order product name	55 W 2GX13 Warm white Circular fluorescent
Power Consumption	55.7 W		

MASTER TL5 Circular

Full product name	55 W 2GX13 Warm white Circular fluorescent
Full product code	871150064279025
Order code	927965783013
Material Nr. (12NC)	927965783013
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.110 kg


EAN/UPC - Product/Case	8711500642790
Numerator - Packs per outer box	10
EAN/UPC - Case	8711500642806

Dimensional drawing




Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
55 W 2GX13 Warm white Circular fluorescent	18 mm	14 mm	293 mm	305 mm	260 mm	272 mm

Photometric data




Spectral Power Distribution Colour - MASTER TL5 Circular 55W/830 1CT/10

Lifetime




Life expectancy diagram - 3 hour cycle



Life expectancy diagram - 12 hour cycle

MASTER TL5 Circular

Lifetime



Lumen Maintenance Diagram - MASTER TL5 Circular 55W/830 1CT/10

