PHILIPS Lighting



MASTER PL-C 2 Pin



MASTER PL-C 18W/830 /2P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- \cdot Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Luminous Efficacy (rated) (Nom)	67 lm/W
Cap-Base	G24d-2	Color rendering index (CRI)	82
Flux measurement reference	Sphere		
Life to 50% Failures (Nom)	10,000 hour(s)	Operating and Electrical	
		Power Consumption	18.3 W
Light Technical		Lamp Current (Nom)	0.230 A
Color Code	830 [CCT of 3000K]		
Luminous Flux	1,200 lm	Controls and Dimming	
Color Designation	Warm White (WW)	Dimmable	No
Chromaticity Coordinate X (Nom)	0.44		
Chromaticity Coordinate Y (Nom)	0.403		
Correlated Color Temperature (Nom)	3000 K		

MASTER PL-C 2 Pin

Mechanical and Housing	
Net Weight (Piece)	57.800 g
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	1.4 mg
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	19 kWh
EPREL Registration Number	423283


Full product name	MASTER PL-C 18W/830 /2P 1CT/5X10BOX	
Full product code	871150062091070	
Order code	927905783040	
Material Nr. (12NC)	927905783040	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8711500620910	
Numerator - Packs per outer box	50	
EAN/UPC - Case	8711500715777	

Product Data


Order product name MASTER PL-C 18W/830 /2P 1CT/5X10BOX

Product D (max) D1 (max) A (max) B (max) C (max) 27.1 mm 27.1 mm 109.5 mm 128.0 mm 150.4 mm MASTER PL-C 18W/830 /2P 1CT/ 5X10BOX

Dimensional drawing




Photometric data



Spectral Power Distribution Colour - MASTER PL-C 18W/830 /2P 1CT/5X10BOX

MASTER PL-C 2 Pin

Lifetime



Life expectancy diagram - 3 hour cycle

Lumen Maintenance Diagram - MASTER PL-C 18W/830 /2P 1CT/5X10BOX

Life expectancy diagram - 12 hour cycle



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2025, February 20 - data subject to change